


5x20mm Glass Fuses

Features

- Quick blow (F) IEC127-2/2
- Glass cartridge, nickel plated end caps
- Break capacity 35A/250V or 10 x In whichever is greater at above 3.5A
- Approvals: SEMKO, VDE, UL and BSI 160mA to 6.3A
- Colour coded available
- Axially centred element



Glass 5x20mm




Type No.	Rating	Type No.	Rating
CF0520F/32	32mA	CF0520F/800	800mA
CF0520F/40	40mA	CF0520F/1	1A
CF0520F/50	50mA	CF0520F/1.25	1.25A
CF0520F/63	63mA	CF0520F/1.6	1.6A
CF0520F/80	80mA	CF0520F/2	2A
CF0520F/100	100mA	CF0520F/2.5	2.5A
CF0520F/125	125mA	CF0520F/3.15	3.15A
CF0520F/160	160mA	CF0520F/4	4A
CF0520F/200	200mA	CF0520F/5	5A
CF0520F/250	250mA	CF0520F/6.3	6.3A
CF0520F/315	315mA	CF0520F/8	8A
CF0520F/400	400mA	CF0520F/10	10A
CF0520F/500	500mA	CF0520F/12.5	12.5A
CF0520F/630	630mA		

Features

- Time delay (T) IEC127-2/3
- Glass cartridge, nickel plated end caps
- Break capacity 35A/250V or 10 x In whichever is greater at above 3.5A
- Approvals: SEMKO, VDE, UL and BSI 125mA to 6.3A
- Colour coded available
- Spiral Element or Plated Solder Section for Superior Characteristics
- Axially Centred Element



Glass 5x20mm



Type No.	Rating	Type No.	Rating
CF0520T/32	32mA	CF0520T/800	800mA
CF0520T/40	40mA	CF0520T/1	1A
CF0520T/50	50mA	CF0520T/1.25	1.25A
CF0520T/63	63mA	CF0520T/1.6	1.6A
CF0520T/80	80mA	CF0520T/2	2A
CF0520T/100	100mA	CF0520T/2.5	2.5A
CF0520T/125	125mA	CF0520T/3.15	3.15A
CF0520T/160	160mA	CF0520T/4	4A
CF0520T/200	200mA	CF0520T/5	5A
CF0520T/250	250mA	CF0520T/6.3	6.3A
CF0520T/315	315mA	CF0520T/8	8A
CF0520T/400	400mA	CF0520T/10	10A
CF0520T/500	500mA	CF0520T/12.5	12.5A
CF0520T/630	630mA		

SERIES
 LED's
 MINIATURE SWITCHES
 INTERFACE MODULES & SUPPORTS
 ENCLOSURES
 IC & PLC SOCKETS
 RELAY BASES
 CONTROL PRODUCTS

5x20mm Ceramic Fuses


Features

- Quick blow (F) IEC127-2/1
- Ceramic cartridge, nickel plated end caps
- High break capacity 1500A/250V
- Approvals: SEMKO
- Axially centred element
- Sand filled

Ceramic 5x20mm



Ceramic 5x20mm



Features

- Time delay (T) IEC127-2/5
- Ceramic cartridge, nickel plated end caps
- High break capacity 1500A/250V
- Approvals: SEMKO
- Axially centred element
- Sand filled

Ceramic 5x20mm



Type No.	Rating	Type No.	Rating
CF0521CF/50	50mA	CF0521CF/1	1A
CF0521CF/63	63mA	CF0521CF/1.25	1.25A
CF0521CF/80	80mA	CF0521CF/1.6	1.6A
CF0521CF/100	100mA	CF0521CF/2	2A
CF0521CF/125	125mA	CF0521CF/2.5	2.5A
CF0521CF/160	160mA	CF0521CF/3.15	3.15A
CF0521CF/200	200mA	CF0521CF/4	4A
CF0521CF/250	250mA	CF0521CF/5	5A
CF0521CF/315	315mA	CF0521CF/6.3	6.3A
CF0521CF/400	400mA	CF0521CF/7.5	7.5A
CF0521CF/500	500mA	CF0521CF/8	8A
CF0521CF/630	630mA	CF0521CF/10	10A
CF0521CF/800	800mA	CF0521CF/12.5	12.5A

Type No.	Rating	Type No.	Rating
CF0521CT/50	50mA	CF0521CT/1	1A
CF0521CT/63	63mA	CF0521CT/1.25	1.25A
CF0521CT/80	80mA	CF0521CT/1.6	1.6A
CF0521CT/100	100mA	CF0521CT/2	2A
CF0521CT/125	125mA	CF0521CT/2.5	2.5A
CF0521CT/160	160mA	CF0521CT/3.15	3.15A
CF0521CT/200	200mA	CF0521CT/4	4A
CF0521CT/250	250mA	CF0521CT/5	5A
CF0521CT/315	315mA	CF0521CT/6.3	6.3A
CF0521CT/400	400mA	CF0521CT/7.5	7.5A
CF0521CT/500	500mA	CF0521CT/8	8A
CF0521CT/630	630mA	CF0521CT/10	10A
CF0521CT/800	800mA	CF0521CT/12.5	12.5A