



3.5mm Pitch Ultra Low Profile Rising Clamp Terminal

- 2-12 pole interlocking
- Ultra low profile
- Moulded in green UL94-V0 flame retardant PA
- Professional rising clamp terminals
- 0.75mm² cable entry
-  approved
- Captive screws
- Guided pin alignment
- Double interlock mechanism for increased strength


CTB0305



Type No.	Poles	Length
CTB0305/2	2	7mm
CTB0305/3	3	10.5mm
CTB0305/4	4	14mm
CTB0305/5	5	17.5mm
CTB0305/6	6	21mm
CTB0305/7	7	24.5mm
CTB0305/8	8	28mm
CTB0305/9	9	31.5mm
CTB0305/10	10	35mm
CTB0305/11	11	38.5mm
CTB0305/12	12	42mm

Rating	10A/130V, UL=10A, CUL=10A, IMQ=10A, VDE=10A
Dielectric strength	2.5kV
Working temperature	110°C
Moulding	UL94-V0 flame retardant PA
Pin/terminal	Tinned, nickel plated brass
Screw/torque	M2 steel, zinc colour plated 0.3Nm
Recommended PCB hole size:	ø1.1mm


3.5mm Pitch Ultra Low Profile 90° Rising Clamp Terminal

- 2-12 pole interlocking
- Ultra low profile
- Moulded in green UL94-V0 flame retardant PA
- Professional rising clamp terminals
- 0.75mm² cable entry
-  approved
- Captive screws
- Guided pin alignment
- Double interlock mechanism for increased strength

CTB0355



CTB0355 Series



For other dimensions see CTB0305

Type No.	Poles	Length
CTB0355/2	2	7mm
CTB0355/3	3	10.5mm
CTB0355/4	4	14mm
CTB0355/5	5	17.5mm
CTB0355/6	6	21mm
CTB0355/7	7	24.5mm
CTB0355/8	8	28mm
CTB0355/9	9	31.5mm
CTB0355/10	10	35mm
CTB0355/11	11	38.5mm
CTB0355/12	12	42mm

Rating	10A/130V, UL=10A, CUL=10A, IMQ=10A, VDE=10A
Dielectric strength	1.5kV
Impulse withstand voltage	2.5kV
Working temperature	110°C
Moulding	UL94-V0 flame retardant PA
Pin/terminal	tinned, nickel plated brass
Rising clamp	Nickel plated brass
Screw/torque	M2 steel, zinc colour plated 0.3Nm
Recommended PCB hole size	ø1.1mm