

### 7.62mm Pitch High Current 90° Rising Clamp Terminal

- 2 & 3 pole double interlocking mechanism for increased strength
- 4-12 pole pre-assembled
- Moulded in green UL94-V0 flame retardant PA
- Professional rising clamp terminals
- 4mm<sup>2</sup> cable entry
- CE, UL, RoHS, REACH, approved
- Guided pin alignment
- Captive screw



CTB07HL series

Type No.	Poles	Length
CTB07HL/2	2	15.24mm
CTB07HL/3	3	22.86mm
CTB07HL/4	4	30.48mm
CTB07HL/5	5	38.10mm
CTB07HL/6	6	45.72mm
CTB07HL/7	7	53.34mm
CTB07HL/8	8	60.96mm
CTB07HL/9	9	68.58mm
CTB07HL/10	10	76.20mm
CTB07HL/11	11	83.82mm
CTB07HL/12	12	91.44mm

#### Specification

Rating	24A/750V, UL=16A, CUL=16A, IMQ=24A, VDE=24A
Dielectric strength	≥3kV/60sec
Insulation resistance	≥5MΩ
Working temperature	-20°C to 125°C
Short period	160°C
Moulding	UL94-V0 flame retardant PA68
Pin/terminal	5μ tinned, nickel plated brass
Wire clamp	Nickel plated brass
Screw/torque	M3 steel, 6μ zinc colour passivated and tropicalised/0.5Nm

Recommended PCB hole size  $\varnothing$ 1.3mm

