

## 10.16mm Pitch **Very High Power** Terminal block

- 2&3 pole solid block
- 2&3 pole double interlocking mechanism for increased strength
- 4 to 12 pole solid block
- Captive screws
- Moulded in grey UL94-V0 flame retardant PA
- Professional rising clamp terminals
- 10mm<sup>2</sup> cable entry



Rating	57A/630V, UL=40A, CUL=40A, IMQ=57A, VDE=57A
Dielectric strength	≥3kV
Impulse withstand voltage	8kV
Working temperature	110°C
Moulding	UL94-V0 flame retardant Lexan
Pin/terminal	Tinned, nickel plated brass
Rising clamp	Zinc plated steel
Screw/torque	M2.5 steel, zinc colour plated/0.4Nm
Recommended PCB hole size	ø1.5mm

Type No.	Poles	Length
CTB77VP/2	2	20.32mm
CTB77VP/3	3	30.48mm
CTB77VP/4	4	40.64mm
CTB77VP/5	5	50.8mm
CTB77VP/6	6	60.96mm
CTB77VP/7	7	71.12mm
CTB77VP/8	8	81.28mm
CTB77VP/9	9	91.44mm
CTB77VP/10	10	101.6mm
CTB77VP/11	11	111.76mm
CTB77VP/12	12	121.92mm

